

## Carbocord ® / 10 Oil and petrol resistant discharge hose

Image not found or type unknown



### Technical specifications:

Oil and petrol delivery hose which is suitable for multi purposes. It's persistent against mineral oil products, up to max 50% aroma content.

The hose is often used during the loading and unloading of unleaded fuels with a maximum aromatic content up to 50% in fuel tanks and ships. Suitable for industrial oils, biodiesel, fuels oils and mineral based hydraulic oils.

The hose inner tube is conductive, the cover anti-static.

**Felirat:** ® CARBOCORD® - NBR - DRUCK / DISCHARGE - PN 10 BAR - Ω

**Working pressure:** 10 bar

**Burst pressure:** 30 bar

**Temperature:** -40°C /+90°C max. olaj hőfok 100 C

**Inside:** NBR, fekete, sima, Elektromosan vezetőképes  $R < 10^6 \Omega$

**Outside:** SBR/EPDM, fekete, szövetlenyomatos, antisztatikus  $R < 10^9 \Omega$

**insertions:** textile plies

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside diameter (mm)	Wall thickness (mm)	Outer diameter (mm)	Bending radius (mm)	Weight (kg/m)	Coil length	Article Nr.
32	6	44	210	1	40	3310 032000
38	6,5	51	300	1,28	40	3310 038000
50	7	64	400	1,75	40	3310 050000