

# Carboflex/10 Oil and petrol resistant suction/discharge tanker truck hose

Image not found or type unknown



## Technical specifications:

It's persistent against mineral oil products, up to max 40% aroma content.

It's in stock with rare diameters too:

With 19, 35, 55, 70, 80, 110 mm inside diameters!

**Felirat:** ® CARBOFLEX® NBR - ÖL SAUG/DRUCK - OIL SUCTION/DISCHARGE - PN 10 BAR - Ω

**Üzemi nyomás:** 10 bar

**Repsztsési nyomás:** 30 bar

**Hőállóság:** -25°C/+90°C

**Belül:** NBR, fekete, sima

**Kívül:** SBR/EPDM, fekete, szövetlenyomatos, kopás- és ózonálló

**Betétek:** acéldrót spirállal és textil betéttel

**Vákuum:** -0,9 bar

**Elektromos ellenállás tömlőbelső:** <math>10^6 \Omega</math>

**Elektromos ellenállás belső és külső között:** Antistatic <math>10^9 \Omega</math>

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Tekercsméret (m)	Cikkszám
22	5,5	33	40	3350 022000
25	5,5	36	40	3350 025000
28	5,5	39	40	8330 028002
32	5,5	43	40	3350 032000
35	6	47	40	8330 035002
38	6,5	51	40	3350 038000
40	5	50	40	8330 040006
42	6,5	55	40	3350 042000
45	6,5	58	40	3350 045000
51	6,5	64	40	3350 050000
55	7	69	40	8330 055001
63	7,5	78	40	3350 063000
70	7	84	40	3350 070000
75	8	91	40	3350 075000
80	8	96	40	3350 080000

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Tekerésméret (m)	Cikkszám
90	8	106	40	3350 090000
100	8	116	40	3350 100000
110	8	126	40	8330 110003
127	8,5	144	20	3350 125000
152	11	174	20	3350 150000