

## GHIBLI-SPECIAL Abrasion resistant hose system with an outer connection



### Technical specifications:

It is suitable for sandblasting systems and hydraulic or pneumatic delivering of abrasive medium. Usually, it is used at construction sites, boat building, mining and other areas of the industry. Abrasion resistant hose system.

The hose length manufactured by the customer's requirements. Several designs are possible. Request a quotation!

**Operating pressure:** 12 bar

**Bursting pressure:** 36 bar

**Heat resistance:** -30°C/+70 °C (for short time +80 °C)

**Interior:** NR/BR rubber, black, electrically conductive, smooth

**Exterior:** synthetic rubber, black, smooth, fabric imprinted, abrasion resistant ozone and weather resistant

**Elektromos ellenállás:** 106Ω

Just for order!

DN	Outside Ø (mm)	Wall thickness (mm)	Bending radius (mm)	Operating pressure (bar)	Weight (kg/m)	Article number
50	72	11	500	12	2,48	230021
80	105	12,5	800	12	4,17	230081
100	125	12,5	1000	12	5,03	230015
125	150	12,5	1250	12	6,26	230032
150	178	14	1500	12	8,44	230037



TRIASZ-TÖMLŐ KFT.

**IMAGE**

**NOT**

**FOUND**

[www.triasztomlo.hu](http://www.triasztomlo.hu)