

CP HiTex 467 Welding Clamp profile hose (clip hose) for flying sparks or welding sparks, (to +280°C)

Image not found or type unknown



Technical specifications:

APPLICATIONS

- flexible hose/ ducting for gases and for dust, powder, fibres
- welding fume extraction
- extraction arm

PROPERTIES

- very good resistance to flying sparks and welding sparks
- fabric reinforced
- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- extremely heat resistant
- flame-retardant
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

TEMPERATURE RANGE

- -70°C to 260°C
- short time to 280°C

DELIVERY VARIANTS

- further diameters and lengths available on request
- black (standard)
- stainless steel (INOX) clamp profile
- double-layer

DESIGN

- CP construction
- 1. clamp profile supporting spiral: galvanised steel
- 2. fabric-reinforced tape; wall: special-coated high-temperature fabric

Temperatur resistance: -70°C / +260°C (rövid ideig +280°C)

Construction: nagy hőállóságú többrétegű szövet

Inside: Fekete

outside: Fekete, külső hoganyzott acél spirállal

Manufacturing length: 3 és 6 m – más hosszokban is gyártható

Will be manufactured with short delivery time. MOQ 3 m

Inner diameter (mm)	Outer diameter (mm)	Working pressure (bar)	Vacuum (bar)	Bending radius (mm)	Article Nr.
80	92	0,6	0,12	24	467-0080-0000
100-102	112	0,52	0,09	28	467-0100-0000
120	132	0,35	0,06	32	467-0120-0000
150-152	162	0,22	0,04	38	467-0150-0000
200-203	212	0,15	0,02	48	467-0200-0000
250	262	0,1	0,012	58	467-0250-0000
350	362	0,055	0,006	78	467-0350-0000

IMAGE

NOT

FOUND

www.triasztomlo.hu

IMAGE

NOT

FOUND

www.triasztomlo.hu