

Purflex / HX Strong polyurethane suction/discharge hose - COPY - COPY

Image not found or type unknown



Technical specifications:

It is suitable for gravel, sand, grains and other abrasive medium and good for heavy-duty industrial vacuum cleaners. The hose is oil, gasoline, crush resistant, and more flexible than the Purflex/SH.

Hőállóság: -40°C/+90°C, rövid ideig +125 C

Szabvány: DIN 26057 Type 4

Tekercsméret: 5-10-15 m

Falvastagság: 2-2,5 mm

Elektromos ellenállás: R < 109 Ohm

On stock at the manufacturer, short delivery time with regular shipments

Belső Ø (mm)	Külső átmérő (mm)	Vákuum (bar)	Nyomás 20°C-on (bar)	Hajlítási sugár mm	Súly (kg/m)	Norres cikkszám	Cikkszám
32	43	-1,00	5,23	90	0,68	356-0032-1001	999500
38*	49	-1,00	4,47	104	0,79	356-0038-1001	
40*	51	-1,00	4,27	109	0,82	356-0040-1001	999308
50	61	-1,00	3,47	134	1,00	356-0050-1001	999152
51*	62	-1,00	3,20	134	1,02	356-0051-1001	
60*	71	-1,00	2,92	156	1,18	356-0060-1001	
63*	74	-1,00	2,81	163	1,23	356-0063-1001	
65*	76	-1,00	2,70	169	1,27	356-0065-1001	
70*	82	-1,00	2,52	186	1,37	356-0070-1001	
75*	87	-1,00	2,36	195	1,48	356-0075-1001	
76*	88	-1,00	2,35	195	1,47	356-0076-1001	
80*	92	-1,00	2,22	205	1,55	356-0080-1001	
100*	113	-1,00	1,98	272	2,27	356-0100-1001	
102*	115	-1,00	1,89	272	2,31	356-0102-1001	
125*	138	-0,89	1,59	363	2,80	356-0125-1001	
127*	140	-0,89	1,56	336	2,84	356-0127-1001	

*egyedi gyártású átmérők



IMAGE

NOT

FOUND

www.triasztomlo.hu

IMAGE

NOT

FOUND

www.triasztomlo.hu